

SARBE Evo New Battery Accessories

SARBE 6-406G Evo Battery Pack (1001744)

High Performance non-rechargeable Lithium Manganese Dioxide battery pack. High impact resistant plastic housing that is ultrasonically welded. Waterproof to 10 meters.



For use with:	SARBE 6-406G Evo; SARBE G2R Evo
NATO Stock number	6135-14-592-8093
Cell Chemistry	Lithium Manganese Dioxide
Nominal Voltage	6 V
Typical Capacity	5.6 Ah
Quantity of Lithium	4.4 g per battery pack
Operational Duration	
SARBE 6-406 Evo	>24 hrs at -20 °C
SARBE G2R Evo	>16 hrs at -20 °C
Nominal Dimensions	75 mm x 55 mm x 42 mm
Weight net	190 g
Case Material	Ultem 1000 Polyetherimide
Operating Temperature	-20 °C to +55 °C
Battery pack life	5 years from manufacturing date. Expiry date marked on battery pack.
Disposal	Check with local regulations
Transport	UN3090 Class 9 Lithium Metal Batteries Packing group II By air: Packing instructions 968 IA By road: Packing instructions 903

SARBE Evo Reset Kit (1001779)

Used with software to reset beacon battery test counters when a new battery is fitted.

